## SPIDERTECH



This LED Channel is ideal for installations that require balanced, dual-direction lighting with a stylish and professional finish.

0.7050 in

[17.91 mm]

0.0270 in

[0.69 mm]

0.0270 in

[0.69 mm] 0.5824 in

[14.79 mm]

R0.0114 in

[R0.29 mm]

Specification Sheet

## **ST- Led Channel 9**

The Spidertech aluminum LED Channel # 9 offers dual lighting—both upward and downward—with a cove-shaped profile for enhanced upper light distribution. It also features a powder-coated finish available in white or bronze. Key features include:

- Material: High-quality aluminum for optimal heat dissipation and long-lasting durability.

- Dual lighting design: Provides both upward and downward illumination, ideal for creating ambient and task lighting in one fixture.

- Cove-shaped profile: The upper part of the channel features a cove design that softens and spreads the upward light, creating a refined ambient glow.

- Powder coating finish: Available in elegant white or bronze finishes, providing both style and durability.

- Integrated Hook & Loop system: Equipped with a Hook & Loop system for easy, tool-free installation.

- Easy maintenance: The channel can be removed and reinstalled with ease, perfect for spaces with limited access.

- Compatibility: Works with all standard LED strips.

- Balanced light distribution: The combination of upward and downward lighting enhances overall illumination, making it ideal for highlighting both ceilings and walls

- Elegant appearance: The sleek design and powder-coated finish add a sophisticated touch to any lighting project.



 STRAIGHTNESS: .0125 PER FOOT
 TWIST: 1° PER FOOT, 7° TOTAL
 FLATNESS: .004 PER INCH

 UNMARKED WALLS: .040
 UNMARKED CORNERS: .010
 CLASS: SOLID
 MATERIAL: ALUM. 6063-T5

 UNLESS OTHERWISE NOTED ALL DIMENSIONS WILL CONFORM TO THE ALUMINUM ASSOCIATION PUBLISHED STANDARDS

0.0270 in

[0.69 mm]

0.1829 in

[4.64 mm]